## **©OUTLANDER™ 6x6 DPS™ 650**

## HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg capacity Dual-Level™ cargo box with modular accessories
- 850 kg towing capacity
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- 12-in, cast-aluminum wheels

- · Relocated air intakes
- Quick release rear sway bar
- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory
- RF Digitally Encoded Security System (D.E.S.S.™)



Green

ENGINE	650
Туре	59 hp, Rotax 649.6 cc V-twin liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC <sup>TM</sup> ) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 25.1 cm travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHE	ELS
Front Tires	Carlisle ACT radial 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle ACT radial 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS /	CAPACITIES
LxWxH	297 x 122 x 126 cm
Wheelbase	208.1 cm
Ground Clearance	27.9 cm
Seat Height	87.7 cm
Dry Weight	545 kg
Rack Capacity	Front: 45 kg Rear: 318 kg
Storage Capacity	Dual-level cargo box with modular accessories Rear: 70 L
Towing Capacity	850 kg
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	Prewired for available winch	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.)

WARRANTY	
Factory	2 years



