200TLANDER MAX 6X6 PRO+ 650 T

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg capacity Dual-Level™ cargo box with modular accessories
- 1,361 kg (3,000 lbs) WARN winch with roller fairlead
- Tri-Mode Dynamic Power Steering (DPS)
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- 12-in. cast-aluminum wheels

- · Relocated air intakes
- · Quick release rear sway bar
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- Digitally Encoded Security System (D.E.S.S.[™])
- Heated hand grips
- Sidewalls and tailgate configuration



	Gree

ENGINES	650
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60 km/h

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 25.1 cm travel
Rear Shocks	Oil

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS				
Carlisle ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)				
Carlisle ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)				
12-in. cast-aluminum				

DIMENSIONS / CAPACITIES			
LxWxH	317 x 122 x 141 cm		
Wheelbase	228 cm		
Ground Clearance	27.9 cm		
Seat Height	87.7 cm		
Dry Weight*	595 kg		
Rack Capacity	Front: 45 kg Rear: 318 kg		
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 70 L		
Towing Capacity	907 kg trailer with brakes and 674 kg trailer without brakes		
Fuel Capacity	20.5 L		

FEATURES				
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)	
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light	
		Seat	Reinforced seat skin	
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)	
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	Heated hand grips	

WARRANIY	- V.		, , ,	A R	۱ III /	NV.
	- 'A'	# * V .	4 4	~ W A		
		# M 1	1 1 1	A 1		

2 years **Factory**



