

2019 OUTLANDER™ MAX PRO+ 570 T

HIGHLIGHTS

- Rotax® V-twin engine
- New arched double A-arm front suspension with front sway bar
- Intelligent Throttle Control (iTCT™) with riding modes
- Continuously Variable Transmission (CVT) with Extra Low L gear
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle† ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- Digitally Encoded Security System (D.E.S.S.™)
- High strength multi-functions racks with LinQ quick-attach accessory
- 21.4 L water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- Raised floorboards
- Heated hand grips
- Mudguards



Green

ENGINES

570

Type	48 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCT™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	Up to 60km/h

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Seat	Convertible Rack System (CRS) with reinforced seat skin
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
		Protection	Heated hand grips, mudguards

WARRANTY

Factory	2 years
---------	---------

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	238.8 x 122 x 135 cm
Wheelbase	149.9 cm
Ground Clearance	30.5 cm
Seat Height	87.7 cm
Dry Weight*	361 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes
Fuel Capacity	20.5 L